

UHF RFID Antennas

ID ISC.ANT.U170/170-EU
ID ISC.ANT.U270/270-EU
ID ISC.ANT.U600/270-EU



FEATURES

- ID ISC.ANT.U600/270-EU:
30° Beam width
- ID ISC.ANT.U170/170-EU:
very small and light shape
- New design
- Circular polarization for
optimal reading performance
- Optimized for operation in
Europe
- IP 65 for outdoor use





UHF RFID Antennas

Order description:

ID ISC.ANT.U170/170-EU
ID ISC.ANT.U270/270-EU
ID ISC.ANT.U600/270-EU

	ID ISC.ANT.U170/170-EU	ID ISC.ANT.U270/270-EU	ID ISC.ANT.U600/270-EU
Dimensions	170 x 170 x 25 mm	270 x 270 x 57 mm	590 x 270 x 57 mm
Housing	ASA-ABS	ASA-ABS	ASA-ABS
Color	White	White	White
Weight	270 g	1.210 g	2.200 g
Protection class	IP65	IP65	IP65
Operating frequency	865-870 MHz	865-870 MHz	865-870 MHz
Gain	4.0 dBic	9.0 dBic	11.0 dBic
3 dB beam width	85° x 85°	65° x 65°	30° x 65°
Polarization	circular	circular	circular
Antenna connection	SMA socket (50 Ohm)	SMA socket (50 Ohm)	SMA socket (50 Ohm)
Temperature range			
Operation	- 25°C up to 55° C	- 25°C up to 55° C	- 25°C up to 55° C
Storage	- 25°C up to 80° C	- 25°C up to 80° C	- 25°C up to 80° C

Available accessories:

Antenna cables ID ISC.ANT.C2-A
ID ISC.ANT.C6-A

Mounting sets ID ISC.ANT.U170/170-MS
ID ISC.ANT.U270/270-MS
ID ISC.ANT.U600/270-MS

Antennas are compatible with any current UHF Reader system.



FEIG ELECTRONIC reserves the right to change specification without notice at any time.
State of information: July 2009.